



SPECIFICATION SHEET



Art Number	JCA-304T
Description	ESD WAVE SOLDERING GLOVE - Textured Nylon 80% - Permanent static dissipative Carbon suffused yarn 20% - Nitrile foam Coating

▷ Detail Information

Size	S-6	M-7	L-8	XL-9	XXL-10
Length(Cm)	22.5	23.5	24.5	25.5	26.5
Surface Resistivity	10 ⁷⁻⁸ Ω		Temperature Resistance	150°C	
Packaged	10pair or 12pair per one poly bag				

▷ Features

- Extra thick for thermal protection **up to 150°C**
- Nylon + conductive carbon/nylon yarn.
- Seamless knit, open back.
- Machine washable for economy of repeated use.
- Permanent static dissipative Carbon(Surface resistivity : 10⁷⁻⁸Ω/sq)

▷ Applications

- Handling delicate and sensitive parts and products, films, eltronic instruments, circuit board and components.
- Assembly-Inspection and repair work in electronics, tele communications, precision instruments and optics,
- Munitions, Aerospace, Photo labs, film handling, electrostatic painting and in the petrochemical industry.

Intermediate Design EN 388:2003 Test Results	
Abrasion Resistance	LEVEL 4
Cut Resistance	LEVEL 3
Tear Resistance	LEVEL 4
Puncture Resistant	LEVEL 3
Dexterity	LEVEL 5

